

Trade name: Tinten- & Kuli-Ex**Product no.:** 197999**Current version :** 1.0.2, issued: 21.12.2020**Replaced version:** 1.0.1, issued: 10.07.2020**Region:** GB**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name****Tinten- & Kuli-Ex****1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

Cleaner

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet**Address**

Koch-Chemie GmbH

Einsteinstr. 42

D-59423 Unna

Telephone no. +49-2303-9 86 70-0

Fax no. +49-2303-9 86 70-26

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

For information in the event of an emergency during transport:

+44 1865 407333

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Aquatic Chronic 3; H412

Eye Dam. 1; H318

Flam. Liq. 3; H226

Skin Sens. 1; H317

STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS02



GHS05



GHS07

Signal word

Trade name: Tinten- & Kuli-Ex

Product no.: 197999

Current version : 1.0.2, issued: 21.12.2020

Replaced version: 1.0.1, issued: 10.07.2020

Region: GB

Danger

Hazardous component(s) to be indicated on label:

1-methoxy-2-propanol

2-propylheptane-1-ol, ethoxylated

Orange, sweet, ext.

Hazard statement(s)

H226

Flammable liquid and vapour.

H317

May cause an allergic skin reaction.

H318

Causes serious eye damage.

H336

May cause drowsiness or dizziness.

H412

Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271

Use only outdoors or in a well-ventilated area.

P280

Wear protective gloves/protective clothing/eye protection.

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310

Immediately call a POISON CENTER/doctor.

P370+P378

In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

P405

Store locked up.

Supplemental label elements

Regulation (EC) No 648/2004 on detergents (Annex VII):

5-15% non-ionic surfactants

Perfumings

LIMONENE

LINALOOL

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	1-methoxy-2-propanol		
	107-98-2 203-539-1 603-064-00-3 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336	>= 70.00 - < 90.00 wt%
2	2-propylheptane-1-ol, ethoxylated		
	160875-66-1 - - -	Eye Dam. 1; H318 Acute Tox. 4; H302	>= 5.00 - < 10.00 wt%
3	Orange, sweet, ext.		
	8028-48-6 232-433-8	Asp. Tox. 1; H304 Flam. Liq. 3; H226	< 5.00 wt%

Trade name: Tinten- & Kuli-Ex**Product no.:** 197999**Current version :** 1.0.2, issued: 21.12.2020**Replaced version:** 1.0.1, issued: 10.07.2020**Region:** GB

-	Skin Irrit. 2; H315		
01-2119493353-35	Skin Sens. 1; H317		
	Aquatic Chronic 2; H411		

Full Text for all H-phrases and EUH-phrases: pls. see section 16

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing. In case of allergic symptoms, especially respiratory tract related, seek medical help immediately.

After inhalation

Remove affected persons from dangerous area by observing suitable respiratory protection measures. Ensure supply of fresh air. Do not use mouth-to-mouth or mouth-to-nose resuscitation.

After skin contact

Wash immediately with plenty of water for several minutes. Consult a doctor if skin irritation persists.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Get immediate ophthalmic treatment.

After ingestion

Rinse out mouth and give plenty of water to drink. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Water spray jet; Foam; Carbon dioxide; Dry chemical extinguisher

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO); Nitrogen oxides (NO_x); Toxic gases/vapours

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear full protective suit. Run-off water from fire fighting must not be discharged into drains or enter surface water. Containers close to fire should be transferred to a safe place. Cool closed containers exposed to fire with water.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Use personal protective clothing. Keep away from ignition sources.

For emergency responders

Personal protective equipment (PPE) - see section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil. In case of entry

Trade name: Tinten- & Kuli-Ex

Product no.: 197999

Current version : 1.0.2, issued: 21.12.2020

Replaced version: 1.0.1, issued: 10.07.2020

Region: GB

into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

Information regarding safe handling, see section 7. Information regarding personal protective measures, see section 8. Information regarding waste disposal, see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Do not inhale vapours. Avoid contact with eyes and skin. Wash hands before breaks and after work. Remove contaminated clothing and shoes and launder thoroughly before reusing. Have emergency shower available. Provide eye wash fountain in work area.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Isolate from sources of heat, sparks and open flame. Take precautionary measures against electrostatic loading (earthing necessary during loading operations). Use explosion-proof equipment/fittings and non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Keep container tightly closed and dry in a cool, well-ventilated place.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

Substances to be avoided, see section 10.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
	2000/39/EC		
	1-Methoxypropanol-2		
	WEL short-term (15 min reference period)	568	mg/m ³ 150 ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m ³ 100 ppm
	Skin resorption / sensibilisation	Skin	
	List of approved workplace exposure limits (WELs) / EH40		
	1-Methoxypropan-2-ol		
	WEL short-term (15 min reference period)	560	mg/m ³ 150 ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m ³ 100 ppm
	Comments	Sk	

Trade name: Tinten- & Kuli-Ex

Product no.: 197999

Current version : 1.0.2, issued: 21.12.2020

Replaced version: 1.0.1, issued: 10.07.2020

Region: GB

DNEL, DMEL and PNEC values**DNEL values (worker)**

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	1-methoxy-2-propanol			107-98-2 203-539-1	
	dermal	Long term (chronic)	systemic	50.6	mg/kg/day
	inhalative	Long term (chronic)	systemic	369	mg/m³
	inhalative	Short term (acute)	local	553.5	mg/m³
2	Orange, sweet, ext.			8028-48-6 232-433-8	
	dermal	Short term (acute)	local	185.8	µg/cm²
	dermal	Long term (chronic)	systemic	8.89	mg/kg/day
	inhalative	Long term (chronic)	systemic	31.1	mg/m³

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	1-methoxy-2-propanol			107-98-2 203-539-1	
	oral	Long term (chronic)	systemic	3.3	mg/kg/day
	dermal	Long term (chronic)	systemic	18.1	mg/kg/day
	inhalative	Long term (chronic)	systemic	43.9	mg/m³
2	Orange, sweet, ext.			8028-48-6 232-433-8	
	oral	Long term (chronic)	systemic	4.44	mg/kg/day
	dermal	Short term (acute)	local	92.9	µg/cm²
	dermal	Long term (chronic)	systemic	4.44	mg/kg/day
	inhalative	Long term (chronic)	systemic	7.78	mg/m³

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	1-methoxy-2-propanol		107-98-2 203-539-1	
	water	fresh water	10	mg/L
	water	marine water	1	mg/L
	water	Aqua intermittent	100	mg/L
	water	fresh water sediment	52.3	mg/kg
	with reference to: dry weight			
	water	marine water sediment	5.2	mg/kg
	with reference to: dry weight			
	soil	-	5.49	mg/kg
	with reference to: dry weight			
	sewage treatment plant	-	100	mg/L
2	Orange, sweet, ext.		8028-48-6 232-433-8	
	water	fresh water	5.4	µg/L
	water	marine water	0.54	µg/L
	water	Aqua intermittent	5.77	µg/L
	water	fresh water sediment	1.3	mg/kg dry weight
	water	marine water sediment	0.13	mg/kg dry weight
	soil	-	0.261	mg/kg dry weight
	sewage treatment plant	-	2.1	mg/L

Trade name: Tinten- & Kuli-Ex

Product no.: 197999

Current version : 1.0.2, issued: 21.12.2020

Replaced version: 1.0.1, issued: 10.07.2020

Region: GB

secondary poisoning	-	13.3	mg/kg food
---------------------	---	------	------------

8.2 Exposure controls**Appropriate engineering controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn.

Personal protective equipment**Respiratory protection**

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified. Filter A or environment-independent breathing apparatus.

Eye / face protection

Tightly fitting safety glasses (EN 166).

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	butyl rubber		
Material thickness	>	0.5	mm
Breakthrough time	>	240	min

Other

Chemical-resistant work clothes.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

State of aggregation		
liquid		
Form/Colour		
liquid		
clear		
Odour		
fruity		
pH value		
No data available		
Boiling point / boiling range		
No data available		
Melting point/freezing point		
No data available		
Decomposition temperature		
No data available		
Flash point		
Value	34	°C
Ignition temperature		
No data available		

Trade name: Tinten- & Kuli-Ex

Product no.: 197999

Current version : 1.0.2, issued: 21.12.2020

Replaced version: 1.0.1, issued: 10.07.2020

Region: GB

Flammability		
No data available		
Lower explosion limit		
No data available		
Upper explosion limit		
No data available		
Vapour pressure		
No data available		
Relative vapour density		
No data available		
Relative density		
No data available		
Density		
Value	0.92	g/cm ³
Reference temperature	20	°C
Solubility		
No data available		
Partition coefficient n-octanol/water (log value)		
No	Substance name	CAS no.
1	Orange, sweet, ext.	8028-48-6
log Pow	2.78	- 4.88
Method	QSAR	
Source	ECHA	
Viscosity		
No data available		
Particle characteristics		
No data available		

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

Stable at ambient temperature.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Dangerous reactions are not to be expected when handling product according to its intended use.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

strong acids; Alkalies; Oxidizing agents

10.6 Hazardous decomposition products

None, if handled according to intended use.

SECTION 11: Toxicological information

Trade name: Tinten- & Kuli-Ex

Product no.: 197999

Current version : 1.0.2, issued: 21.12.2020

Replaced version: 1.0.1, issued: 10.07.2020

Region: GB

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	Tinten- & Kuli-Ex
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE oral > 2000 mg/kg).

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		4016	mg/kg bodyweight
Species	rat		
Method	EC 440/2008, B.1		
Source	ECHA		
2	Orange, sweet, ext.	8028-48-6	232-433-8
LD50		5000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		2000	mg/kg bodyweight
Species	rat		
Method	440/2008/EC B.3.		
Source	ECHA		
2	Orange, sweet, ext.	8028-48-6	232-433-8
LD50		5000	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA		

Acute inhalational toxicity	
No data available	

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Species	rabbit		
Method	EC 440/2008, B.4		
Source	ECHA		
Evaluation	non-irritant		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Species	rabbit		
Method	2004/73/EEC, B.5		
Source	ECHA		
Evaluation	non-irritant		
2	Orange, sweet, ext.	8028-48-6	232-433-8
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	non-irritant		

Trade name: Tinten- & Kuli-Ex

Product no.: 197999

Current version : 1.0.2, issued: 21.12.2020

Replaced version: 1.0.1, issued: 10.07.2020

Region: GB

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Route of exposure		Skin	
Species		guinea pig	
Method		440/2008/EC B.6	
Source		ECHA	
Evaluation		non-sensitizing	
2	Orange, sweet, ext.	8028-48-6	232-433-8
Route of exposure		Skin	
Species		mouse	
Method		OECD 429	
Source		ECHA	
Evaluation		sensitizing	
Germ cell mutagenicity			
No data available			
Reproduction toxicity			
No data available			
Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	Orange, sweet, ext.	8028-48-6	232-433-8
Method		OECD 451	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
STOT - single exposure			
No data available			
STOT - repeated exposure			
No data available			
Aspiration hazard			
No data available			

11.2 Information on other hazards**Endocrine disrupting properties**

No data available.

Other information

No data available.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	Orange, sweet, ext.	8028-48-6	232-433-8
LC50		5.65	mg/l
Duration of exposure		96	h
Species		Danio rerio	
Method		OECD 203	
Source		ECHA	
Toxicity to fish (chronic)			
No data available			
Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.

Trade name: Tinten- & Kuli-Ex

Product no.: 197999

Current version : 1.0.2, issued: 21.12.2020

Replaced version: 1.0.1, issued: 10.07.2020

Region: GB

1	Orange, sweet, ext.	8028-48-6	232-433-8
EC50		1.1	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

No	Substance name	CAS no.	EC no.
1	Orange, sweet, ext.	8028-48-6	232-433-8
ErC50		150	mg/l
Duration of exposure		72	h
Species	Desmodesmus subspicatus		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Type	aerobic biodegradation		
Value		96	%
Duration		28	day(s)
Method	OECD 301 E		
Source	ECHA		
Evaluation	readily biodegradable		
2	Orange, sweet, ext.	8028-48-6	232-433-8
Source	ECHA		
Evaluation	readily biodegradable		

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)			
No	Substance name	CAS no.	EC no.
1	Orange, sweet, ext.	8028-48-6	232-433-8
BCF		32	- 156
Source	ECHA		

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	Orange, sweet, ext.	8028-48-6	232-433-8
log Pow		2.78	- 4.88
Method	QSAR		
Source	ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

Trade name: Tinten- & Kuli-Ex**Product no.:** 197999**Current version :** 1.0.2, issued: 21.12.2020**Replaced version:** 1.0.1, issued: 10.07.2020**Region:** GB**12.7 Other adverse effects**

No data available.

12.7 Other information**Other information**

Do not discharge into the drains or waters and do not store on public depositories.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information**14.1 Transport ADR/RID/ADN**

Class	3
Classification code	F1
Packing group	III
Hazard identification no.	30
UN number	UN1263
Proper shipping name	PAINT RELATED MATERIAL
Tunnel restriction code	D/E
Label	3

14.2 Transport IMDG

Class	3
Packing group	III
UN number	UN1263
Proper shipping name	PAINT RELATED MATERIAL
EmS	F-E, S-E
Label	3

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	III
UN number	UN1263
Proper shipping name	Paint related material
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

Trade name: Tinten- & Kuli-Ex

Product no.: 197999

Current version : 1.0.2, issued: 21.12.2020

Replaced version: 1.0.1, issued: 10.07.2020

Region: GB

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
EU regulations**Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
--	----------

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:	P5c
--	-----

Other regulations

Adhere to the national sanitary and occupational safety regulations when using this product.
Employment restrictions, according to the regulations for protection of expectant and nursing mothers and the youth health and safety regulations, serving to protect against hazardous materials, should be observed.
The surfactants contained in this product comply with the DetVO 648/2004/EC.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H411	Toxic to aquatic life with long lasting effects.

Creation of the safety data sheet

UMCO GmbH - D-21107 Hamburg, Georg-Wilhelm-Strasse 187, Tel.: +49(40)555 546 300, Fax: +49(40)555 546 357, e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.
Prod-ID 763557

Trade name: Tinten- & Kuli-Ex

Product no.: 197999

Current version : 1.0.2, issued: 21.12.2020

Replaced version: 1.0.1, issued: 10.07.2020

Region: GB
